

## About the Optimum 400 Hydraulic Platform Lift

The Optimum 400 is a high quality and reliable hydraulic platform lift designed to work externally. They come complete with a self supporting glazed structure and have side opening landing doors or an upper level landing gate. These units are compliant with building regulations. We are also pleased to offer adjacent entry if required.

## Standard Features

- Three standard platform sizes
- Single piece self-closing doors
- Half-Height gates at upper level up to 3m travel
- Full-height doors at upper level above 3m travel
- 24v DC controls
- Arrival Chimes
- Platform/Carriage Lighting
- Emergency battery lowering
- 7000mm travel
- 0.08m/sec travel speed
- 400kg SWL
- Fully panelled shaft walls
- In car overload protection
- CE Marked



## Specifications

- Platform rated load 400kg
- Travel distance up to 6 metres
- Travel speed 0.08 metres/second
- Power supply 240v, single phase, 50Hz
- Platform sizes
  - 1400mm x 1100mm
  - 1400mm x 900mm
- 1250mm x 900mm
- Footprint sizes
  - 1520mm x 1380mm
  - 1520mm x 1180mm
  - 1370mm x 1180mm
- Pit Depth 60mm or ramp can be specified
- Headroom 2300mm minimum headroom required

## Contact Us

Ability Lifts Limited  
Khepera Business Centre  
9, Orgreave Road, Sheffield  
S13 9LQ

Tel: 0845 006 8803  
Email: [sales@abilitylifts.co.uk](mailto:sales@abilitylifts.co.uk)  
Web: [www.abilitylifts.co.uk](http://www.abilitylifts.co.uk)